MuCis[®] MIA 100

Migrating Multifunctional Fixative Corrosion Inhibitor

MuCis[®] MIA 100 is a multifunctional corrosion inhibitor. It protects the reinforcements by anodic and cathodic reaction, as contact and migration inhibitor.

Uses

MuCis[®] MIA 100 is recommended for all structures in reinforced concrete, normal or precompressed, particularly when used in heavy stressed environments like bridges, viaducts, garages, parking lots, marine structures, etc.

Benefits

- MuCis[®] MIA 100 can be used as such to protect the steel bars of the reinforcement against corrosion reactions, cathodic or anodic.
- Migrates through the concrete and it reaches the capillarity and the internal steel bars.
- Inhibits corrosion processes. Does not contain any nitrites, it is an organic solution in water.
- Non-toxic liquid system, user friendly application, easy to apply by brush, roller or spraying.

Technical Support

The company provides a technical advisory service supported by a team of specialists in the field.

Properties

| Appearance | Yellow/Amber Liquid |
|------------|---------------------|
| рН | 10-12 |

Method of use

Apply in 1 or 2 layers with an interval of 8 hours. In the case of mortar to be applied next. Use the special mortars as specified in our systems for better adhesion.

Precaution

Do not apply at temperature lower than +1°C. Apply on clean, sound and dry substrates without old paints, fats, oil or other foreign substances.

Health & Safety Instructions

Read carefully the safety indications on the packaging, or consult the relevant safety data sheet of this product.



Storage

Keep it away from frost. It can be kept for 24 months in original unopened packaging.

Packing

 ${\rm MuCis}^{^{(\!\!\!\!R)}}\,{\rm MIA}$ 100 is available in cans of 5 ltr & 20 ltr. drums of 210 ltr.

Coverage

From 250 to 450 ml/sq.m/coat as per site condition requirement.

MuCis[®] MIA 100



Thermax Limited Environment House, Plot No.90-92 BG Block, MIDC, Bhosari, Pune 411 026, India. Tel: +91-20-67156000 Fax: +91-20-27120206 Customer Care: 18002090115 (India toll free) Email : enquiry@thermaxglobal.com

Ahmedabad

Tel: +91-79-26575408 • Fax: +91-79-65577270

Bengaluru

Tel: +91-80-22371721 • Fax: +91-80-22371726

Chennai

Tel: +91-44-24303400 • Fax: +91-44-24353841

Delhi

Tel: +91-11- 46087200 • Fax: +91-11- 26145311

Hyderabad

Tel: +91-40-23253700 • Fax: +91-40-23253799

Kolkata

Tel: +91-33-66070800 • Fax: +91-33-66070999

Mumbai

Tel: +91-22-67542222 • Fax: +91-22-22040859

Thermax World-wide

UK, USA, UAE, Germany, Belgium, Denmark, Russia, Saudi Arabia, Thailand, Malaysia, Bangladesh, Sri Lanka, China, Philippines, Peru, Chile, Kenya, Nigeria, Brazil, Indonesia

Website: www.thermaxglobal.com

Thermax Business Portfolio

Chemicals

Absorption Cooling

Air Pollution Control

Boilers & Heaters

Power

Water & Waste Solutions

Other Segments:

Concrete Admixtures
Surface Treatments
Grouts & Anchors
Repair & Rehabilitation

Protective Coatings
Industrial Flooring
Waterproofing
Sealants
Adhesives

Disclaimer: The information contained in this document is true and accurate to the best of our knowledge and is based on our experience & test results. It is always the Company's endeavor to give true and accurate information however as it does not have any direct and/or continuing control on the use of the Products, the Company cannot accept any liability, direct or indirect as a consequence of the use of Products. In the event of any doubt upon any critical parameter it is advisable to seek clarification from our technical representative.

We reserve the right to amend any product details without notice. Copyright © Thermax Limited Edition: (TCC/TDS/0420)

Solar